



BA-PHALABORWA MUNICIPALITY

- BUDGET AND TREASURY –

- PROCUREMENT AND STORES -

TO : Prospective Service Provider  
FROM : SCM/STORES  
DATE : 21/09/2016  
ENQUIRIES : STORES  
TELEPHONE : 015 780 6362/61  
REF : 126239

Kindly furnish this office with a written quotation for supply of goods/ services as detailed below. The quotation must be submitted on the letterhead of your Business and Brought to our offices/ emailed to [MogofeN@ba-phalaborwa.gov.za](mailto:MogofeN@ba-phalaborwa.gov.za) or not later than 29/09/2016 at 12HOO.

QUANTITY	Description	PRICE/UNIT (Inc .VAT)	UOM
02	Bitumen emulsion sprayer		Each
	<b>See attached specs below</b>		

**Please number your quotes (Your Ref no)**

The following conditions will apply:

- Price (s) quoted must be valid for **at least thirty (30) days** from date of your offer.
- The municipality retains the prerogative to reject any quotes it deems to be excessive
- A firm delivery period must be indicated.
- Original Tax Clearance Certificate
- A service provider be registered with Ba-Phalaborwa database
- Registered with CIPRO (CK 1 or 2 document)
- BBBEE Certificate certified by a SANAS accredited institution.
- Fill in and Return the Declaration of Interest Form.
- CSD registration summary report

The municipality reserves a right not to appoint on the advertised



BA-PHALABORWA MUNICIPALITY

- BUDGET AND TREASURY –

- PROCUREMENT AND STORES -

## Bitumen Emulsion Sprayer, S-TMBSHOT



S-TMBSHOT

- Engine: GX160HX -6:1 reduction engine
- Pump: Gear pump with maximum delivery of 18Lt per minute
- Lance: Length - 2m with handle and shut off valve
- Nozzle: 2 x 65 Deg. flat spray adjustable nozzles
- Hose: 3m long - oil resistant type hose
- Wheels: 350mm x 100mm Rubber wheels

The TMBSHOT, for hot bitumen spraying and TMBSC, for cold bitumen spraying units are built onto a robust chassis and is ideal for all bitumen spraying conditions.

Maintenance can easily be done by dismantling all working parts of the pump. The pump is fitted with a built in bypass system. This system allows the spraying function to be interrupted, or reduced at any time. The system accommodates a 210Lt drum. The hot bitumen sprayer is supplied with a gas regulator and gas carrying bottle brackets only. Both machines offer excellent maneuverability through a lightweight and robust design

<b>Model</b>	<b>Description</b>
S-TMBSC	Bitumen Emulsion Sprayer, S-TMBSC