

Black and White	Resolution	Up to 600 x 600 dpi
	Speed	Up to 30 ppm (Black Only)
	Connectivity	IEEE 1284-compliant parallel port, one Hi-Speed USB 2.0 port
	Warranty	One-year return to depot
	Functions	Print
	Duty Cycle	Up to 25000 pages
	Market positioning	Home & Office
	Colour of product	White
	Built-in display	No
	Display	No
	Colour of product	White
	Colour	No
	Maximum resolution	600 x 600 DPI
	Maximum duty cycle	25000 pages per month
	Number of print cartridges	1
	Standard printer languages	PCL 5e
	Print technology	Laser
	Recommended duty cycle	500 - 2500 pages per month
	Maximum duty cycle	25000 pages per month
	Number of print cartridges	1
	Print speed (black, normal quality, A4/US Letter)	30 ppm
	Time to first page (black, normal)	8 s
	Multi-Purpose tray capacity	50 sheets

2	Number of standard paper trays
150 sheets	Standard output capacity
150 sheets	Maximum output capacity
A4	Maximum ISO A-series paper size
Bond paper, Card stock, Envelopes, Heavy paper, Heavy media, Labels, L Recycled paper, Rough paper, Transparencies	Standard tray media types
A4	ISO A-series sizes (A0...A9)
Executive, index card, Letter, Statement, Legal	Non-ISO print media sizes
60 - 163 g/m ²	Standard tray media weight
No	Ethernet LAN
No	Network ready
Parallel,USB 2.0	Standard interfaces
1	USB 2.0 ports quantity
16 MB	Internal memory
16 MB	Maximum internal memory
Yes	Built-in processor
266 MHz	Processor frequency
550 W	Power consumption (typical)
7 W	Power consumption (PowerSave)
0.4 W	Power consumption (off)
Windows 2000,Windows 2000 Professional,Windows 7 Home Basic,Windows Home Premium,Windows 7 Home Premium x64,Windows 7 Professional, Windows 7 Starter,Windows 7 Starter x64,Windows 7 Ultimate,Windows 7 U	Windows operating systems supported
Mac OS X 10.3 Panther,Mac OS X 10.4 Tiger,Mac OS X 10.5 Leopard,Mac	Mac operating systems supported
Windows Server 2003,Windows Server 2003 x64,Windows Server 2008	Server operating systems supported

Energy Star certified	No
Blue Angel certified	No
Operating temperature (T-T)	15 - 32.5 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	63.5 - 77 °F
Maximum dimensions (W x D x H)	365 x 677 x 268 mm
Width	365 mm
Depth	368 mm
Height	268 mm
Packaging width	481 mm
Weight	10 kg
Pallet dimensions (W x D x H)	1200 x 1000 x 2485 mm
Packaging depth	330 mm
Packaging height	465 mm
Pallet weight	456.7 kg
Package weight	12.4 kg
Cartridge(s) included	Yes
Included cartridge capacity (black)	1000 pages
Software CD	Yes
Quick start guide	Yes
Power cord included	Yes

Print quality (black, normal quality)	600 DPI
Recommended operating temperature range (T-T)	17.5 - 25 °C
Mac compatibility	Yes
I/O ports	1x parallel, 1x USB
Memory upgrade	No
Print margin bottom (A4)	4 mm
Print margin left (A4)	4 mm
Print margin right (A4)	4 mm
Print margin top (A4)	4 mm
Standard output capacity for envelopes	5 sheets
Acoustic pressure emissions (A4)	54 dB
Print speed (black, best quality, A4)	30 ppm
Quantity per pallet	35 pc(s)
Number of layers per pallet	5
Size	36.6 cm (14.4")
Number of cartons per pallet	7
Product dimensions when open (LxWxD)	36.6 cm (14.4")
Standard output capacity for transparencies	75 sheets
Acoustic pressure emissions bystander (active, print, copy or scan)	54 dB(A)
First page out (black&white, A4, ready)	8
Print speed (black, best quality, letter)	> 30 ppm

Pallet weight (imperial)	455.7 kg (1004.7 lbs)
Package dimensions (W x D x H)	480.8 x 330.2 x 464.8 mm (18.9 x 13 x 18.3")
First page out (black&white, letter, ready)	8
Pallet dimensions (W x D x H) (imperial)	1219.2 x 1016 x 2484.1 mm (48 x 40 x 97.8")
Print quality (black, best quality)	600 x 600 DPI
Package weight (imperial)	27.2 lb
First page out (black&white, letter, sleep)	8